

USER INSTRUCTIONS AND IMPORTANT SAFETY INFORMATION

IMPORTANT: Please completely understand all user instructions and safety information before using this product.

TOOLS REQUIRED

4 mm Hex Wrench
8 mm Open-Ended Wrench
Torque Wrench 1.7 Nm (15 in-lbs)



NOTE

The **XENON** cage comes loosely attached to the **DELTA** Mount with 35 mm long screws. The screws are long enough for you to add the recommended XLAB **MULTI-STRIKE REPAIR HOLDER** between the cage and the black spacers. This **DELTA** has one 3/8" black cylindrical spacer on the top, and one 1/4" black cylindrical spacer on the bottom. The spacers are to ensure that even with long saddles, the water bottle will clear the rear of the saddle. There are also two M5 square washers beneath the locking nuts, to allow easy access to the nuts with an 8 mm wrench. The Mount is attached loosely to its backplate with two 15 mm screws with Loctite on the threads that will help prevent the screws from loosening once installed on the saddle.

INSTALLATION INSTRUCTIONS

1. Using a 4 mm Allen Hex Wrench and an 8 mm Open-Ended Wrench, fully tighten the two long screws holding the cage to the Mount. Tighten to 1.7 Nm (15 in-lbs) of torque.
2. Next unscrew the two 15 mm screws from the backplate.
3. Hold the Mount up to the back of the saddle rails and position the backplate inside the rails.
4. Insert the two 15 mm screws through the Mount into the backplate. Hand-tighten and then check that the cage is in the position you require. Tighten to 1.7 Nm (15 in-lbs) of torque. The Loctite on the threads will harden over 24 hours. You can still remove the screws in the future but the Loctite is a one-time use. You can purchase replacement screws with Loctite on the XLAB web store.
5. XLAB **MULTI-STRIKE REPAIR HOLDER** can fit between the cage and the black spacers. To install, remove the 35 mm cage screws and re-assemble with the **MULTI-STRIKE** between the black spacers and cage. Tighten to 1.7 Nm (15 in-lbs) of torque.

MAINTENANCE

As with any high-tech racing gear, you need to routinely check for loose hardware, cracks or other damage and replace as required.

WARRANTY

3 Year warranty on Mount and **XENON** cage. See website for details.